

Metamark MD-AC370

Art Canvas - 370gsm Satin Finish



Product Description

Metamark MD-AC370 is a premium grade satin finish art canvas for tensioned fine art prints. It has a special acrylic coating offering a bright white finish, and giving vibrant colour brilliance with photo realistic definition. The lighter weight allows finer finishing of the framed print. It has an excellent drying time, crack resistance and is water fast. Suitable for fine art prints, stretched over a frame. For other applications the customer should be aware that the product will shrink as a result of the printing process. Shrinkage is minimal.

Material Handling

- Ensure that the material has reached recommended room temperature and a relative humidity before printing.
- Do not handle the face film directly and ensure it is free from dust and static.
- When stretching the canvas over a frame it is recommended to use a frame with a very slightly bevelled edge which will avoid any possible minor cracking.

Printing Guidelines

- Suitable for use on Solvent and Eco Solvent inkjet printers, as well as U.V Curable and HP Latex. Always perform a test print first.
- Ensure that the correct profiles and heater settings are used. Most profiles are available for download from www.metamark.co.uk.
- Allow 24 hours after printing for the ink to gain full abrasion resistance. Do not stack prints until fully cured.
- The product is designed to be used without an overlamine. If a liquid laminate is used it is the responsibility of the user to test.
- The durability of the finished print is dependent on the inks and printer.

Fabric Specifications

Weight	370gsm
Thickness	420 micron
Canvas Structure	1:1
Type of Coating	Satin Finish
Fabric Blend	65% Polyester / 35% Cotton
Print Surface	Single side print face outwards

Finishes

Finish Available	MD-AC370 Satin Finish Art Canvas
------------------	----------------------------------

Roll Presentation

Roll sizes	760mm x 15m 1370mm x 15m 1600mm x 15m
Presentation	Face film outwards

Durability

Storage and processing	30-50% Relative humidity, 10 to 30°C
Fire Rating	None
Durability	Long term indoor and short term outdoor. Water fast.
Regulations	REACH compliant

Warranty: Metamark (UK) Limited warrants to its customers that graphics produced using Metamark Digital Media will remain in good condition without excessive fading or colour degradation for the specified life time of the ink used, when correctly stored, printed and applied in accordance with procedures outlined in the technical literature. If within the specified years of normal use Metamark Digital/Vinyl becomes ineffective for its intended use, then Metamark will provide sufficient material to produce a new replacement marking, and will at its own discretion, contribute an allowance in additional material towards the costs involved in replacing the graphics. In all cases, the converter is held fully responsible for storing, processing and applying the unconverted materials in accordance with Metamark's technical specifications. Metamark (UK) Limited will not be liable for any indirect or consequential loss or damage, and will not provide any allowance against improper usage, application accident, negligence, chemical damage or improper repair. **Please Note:** The above data is given in good faith to provide an indication of the performance of the product. Purchasers should consider the suitability of each product for its intended use and the purchaser assumes all risks in connection with such use. Seller shall not be liable for damages in excess of the purchase price of the product nor for incidental nor consequential loss.

Metamark (UK) Limited

○ Luneside • New Quay Road • Lancaster • LA1 5QP • Tel +44 (0)1524 387140 • Fax +44 (0)1524 387147

○ Metamark House • Octimum Business Park • Forsyth Road • Woking • GU21 5SF • Tel +44 (0)1483 571111 • Fax +44 (0)1483 570540

sales@metamark.co.uk

www.metamark.co.uk