

Metamark MD-AC240

Art Canvas - 400gsm Satin Finish



Product Description

Metamark MD-AC240 is a satin coated art canvas suitable for fine art prints usable for framed art without edge cracking. The natural cotton/polyester product benefits from a warm white satin finished inkjet coating, which is water resistant. Due to the special coating the canvas is suitable for heavy ink loads and uniform area prints also in critical dark tones. The coated surface also offers a good light-stability and excellent colour reproduction.

Material Handling

- Ensure that the material has reached recommended room temperature and a relative humidity before printing.
- Do not handle the face film directly and ensure it is free from dust and static.

Printing Guidelines

- Suitable for use on Solvent and Eco Solvent inkjet printers, as well as U.V Curable and HP Latex. Always perform a test print first.
- Ensure that the correct profiles and heater settings are used. Most profiles are available for download from www.metamark.co.uk.
- Allow 24 hours after printing for the ink to gain full abrasion resistance, before handling.
- When stretching the canvas over a frame it is recommended to use a frame with a very slightly bevelled edge which will avoid any possible minor cracking.
- The product is designed to be used without an overlamine. If a liquid laminate is used it is the responsibility of the user to test.
- As the canvas is natural cotton/polyester it will shrink. This characteristic helps to tension it over the frame.
- The durability of the finished print is dependent on the inks and printer.

Fabric Specifications

Weight	400gsm
Thickness	470 micron
Basic Fabric	1:1 cotton/polyester canvas
Type of Coating	Satin Finish
Fabric Blend	78% Cotton / 22% Polyester
Print Surface	Single side print face outwards

Finishes

Finish Available	MD-AC240 Satin Finish Art Canvas
------------------	----------------------------------

Roll Presentation

Roll sizes	760mm x 15m 1370mm x 15m 1520mm x 15m
Presentation	Print surface outwards

Durability

Storage and Processing	35-65% Relative humidity. 10 to 30°C
Fire Rating	None
Durability	Long term indoor and short term outdoor use. Water-fast.
Regulations	REACH compliant

Warranty: Metamark (UK) Limited warrants to its customers that graphics produced using Metamark Digital Media will remain in good condition without excessive fading or colour degradation for the specified life time of the ink used, when correctly stored, printed and applied in accordance with procedures outlined in the technical literature. If within the specified years of normal use Metamark Digital/Vinyl becomes ineffective for its intended use, then Metamark will provide sufficient material to produce a new replacement marking, and will at its own discretion, contribute an allowance in additional material towards the costs involved in replacing the graphics. In all cases, the converter is held fully responsible for storing, processing and applying the unconverted materials in accordance with Metamark's technical specifications. Metamark (UK) Limited will not be liable for any indirect or consequential loss or damage, and will not provide any allowance against improper usage, application accident, negligence, chemical damage or improper repair. **Please Note:** The above data is given in good faith to provide an indication of the performance of the product. Purchasers should consider the suitability of each product for its intended use and the purchaser assumes all risks in connection with such use. Seller shall not be liable for damages in excess of the purchase price of the product nor for incidental nor consequential loss.

Metamark (UK) Limited

○ Luneside • New Quay Road • Lancaster • LA1 5QP • Tel +44 (0)1524 387140 • Fax +44 (0)1524 387147

○ Metamark House • Octimum Business Park • Forsyth Road • Woking • GU21 5SF • Tel +44 (0)1483 571111 • Fax +44 (0)1483 570540

sales@metamark.co.uk

www.metamark.co.uk